

CE52LH1R *Tentative*

ROBUST LCD Monitor



ROBUST LCD MONITOR

SANYO has used all of its expertise in creating a lightweight aluminum framed LCD monitor which is protected by non-glare acrylic panel. This means that the SANYO robust monitor can be used in a wide variety of environments for dusty and oily circumstance such as fast food, digital signage, industrial and public display

EXTENSIVE INPUT & OUTPUT TERMINALS

The 52LH1R has various input and output terminals including component (Y,Pb,Pr) or RGBHV input and output with 5-BNC, composite video input and output with BNC, and RS-232 control port (serial D-Sub 9) input and output which offer the daisy chain connection. There are computer inputs (a D-Sub 15 RGB terminal) and DVI-D input with HDCP for High definition signals. There are also jacks for an external speakers. Through connecting input and output with 5-BNC, enlarged image will be available by video wall function.

NON GLARE ACRYLIC PANEL

The 52LH1R has a non glare acrylic panel. This offers the protection for the panel surface in the public display applications and easy to clean the panel.

ALUMINUM CABINET & NON HOLES DESIGN

The 52LH1R uses Anodized aluminum and it has quite unique 'Non-Holes' ventilation design which protects against mischief in the public display applications and less maintenance when used in a dusty or oily environment.

OPTIONAL PJ-NET ORGANIZER

An optional network box makes it possible to use a network monitor, using your internet browser to monitor and control the display's properties. Transmitting picture by Network Viewer is available.

SANYO

SANYO Canada Inc.
1-300 Applewood Cres.,
Concord, Ontario. L4K 5C7
Tel. 905-760-9944
www.sanyo.ca

Specifications

Type	Liquid Crystal Display Panel with TFT
Screen Size	52V
Aspect Ratio	16:9
Resolution	High Definition 1920 (H) x 1080 (V) pixels
Brightness	500 (cd/m ² for panel)
Contrast Ratio	1500:1 (typical)
Viewing Angle	178° (Vertical/Horizontal)
Response Time	8ms (gray to gray)
Computer Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA
Speaker	N/A
Colour System	PAL / NTSC3.58(AV-IN) / SECAM
Input Terminals	
AV1	Video / Audio (Scart) / RGB
AV2	Component (Y,Pb,Pr) / RGBHV (BNC x 5) Audio (RCA x 2)
AV3	Video (BNC x1)
Computer 1	RGB (D-Sub 15) Audio (mini-jack)
DVI	DVI-D With HDCP
RS-232	Serial (D-Sub 9)
Output Terminals	Component (Y,Pr,Pb) / RGBHV (BNC x 5)
AV2	Audio (RCA x 2)
AV3	Video (BNC x1)
RS-232	Serial (D-Sub 9)
Audio Monitor Output	Audio (RCA x 2)
External Speaker out	1 Ω W + 60W
Power Supply	AC 100V - 240 V 50 / 60Hz
Power Consumption	T.B.C
Operation Temperature	Operation 0-45 °C (32 - 113 °F)
Dimensions (WxHxD)	1304 x 800 x 236 mm (w/o Option) 51.3" x 31.5" x 9.3" (w/o Option)T.B.C
Net Weight	68 kg.
Packed Dimensions (WxHxD)	152 x 102 x 42 cm. With flat packing
Packed Weight	88 kg.
Included Accessories	Owner's Manual; Remote Control w/Batteries; AC Power Cord
Optional Accessories	PJ-Net Organizer (POAPN03C)
Safety / EMC	EN60950 2002 EN55022 1998+A2 EN55024 1998+A2 EN61000-3/2-2000 -3/3-1995+A1 2001 UL60950 2002 CAN/CSA-C22.2 FCC part15 Class B, UL Listed
Container	T.B.C

Because our products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

We make finding the Writeboard easy

TOUCHBOARDS

1-866-942-6273 .COM

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com