

<b>PRODUCT NAME</b>	<b>LV-7585</b>
<b>ITEM CODE</b>	<b>2473B002AA</b>
<b>UPC CODE</b>	<b>013803089745</b>



**Suggested List Price:**  
**LV-7585: \$9,999.00**

### FEATURES:

- ▲ Genuine Canon Optics: 1.3x Optical Zoom
- ▲ 6500 ANSI Lumens
- ▲ 1600:1 Contrast Ratio
- ▲ ±40° Vertical and ±20° Horizontal Keystone (Manual)
- ▲ 3:2 - 2:3 Horizontal Pulldown
- ▲ Auto-Winding Filter System up to 10,000 hours of usage before replacement
- ▲ New 330W NSHA Longer Lasting AC Lamp
- ▲ 32 dB Noise Level (Quiet Mode)
- ▲ 10-bit Digital Video Processing
- ▲ Optional Lenses
  - Ultra Wide Angle
  - Long Focus Zoom
  - Wide Angle Zoom
  - Ultra Long Focus Zoom

### CANON CUSTOMER SUPPORT:

- ▲ Canon's Triple P (Projector Protection Program):  
A projector loaner is provided if the original projector is in need of repair
- ▲ 3-Year Parts and Labor Warranty - 120 Day Lamp Life Warranty

### CONTENTS OF KIT:

- ▲ LV-7585 Projector
- ▲ USB Mouse Control Cable
- ▲ Wireless/Wired Remote Control
- ▲ Power Cable
- ▲ Wired Remote Cable
- ▲ Warranty Card
- ▲ VGA Computer Cable
- ▲ Pin Code Label
- ▲ User's Manual

### ACCESSORIES:

ITEM CODE NO.	DESCRIPTION	SUGG. LIST PRICE
2541B001AA	LV-CL13 CEILING MOUNT ADAPTER	599.00
2682B001AA	LV-CL14 HIGH CEILING ATTACHMENT	999.00
2542B001AA	LV-LP29 REPLACEMENT LAMP	599.00
7502A001AA	LV-CA29 DVI CABLE	69.00
7667A001AA	LV-IL01 ULTRA WIDE ANGLE LENS	2,500.00
7668A001AA	LV-IL02 WIDE ANGLE ZOOM LENS	2,500.00
7669A001AA	LV-IL03 LONG FOCUS ZOOM LENS	2,500.00
9030A001AA	LV-IL04 ULTRA LONG FOCUS ZOOM LENS	3,000.00
1707B001AA	LV-NI02 NETWORK IMAGER	699.00

### PACKAGING INFORMATION:

PROJECTOR	W x D x H	WEIGHT
LV-7585	19.4 x 24.8 x 15.3 in (492 x 630 x 388 mm)	38.8 lbs (17.6 kg)

## PROJECTOR

### SPECIFICATIONS:

<b>BASICS:</b>	
IMAGING DEVICE	1.3" TFT Poly- Silicon LCD panels x 3
ASPECT RATIO	4:3
NATIVE RESOLUTION	XGA
BRIGHTNESS	6500 ANSI Lumens
UNIFORMITY	90%
CONTRAST	1600:1
KEystone	
VERTICAL	+/- 40 degrees (Manual)
HORIZONTAL	+/- 20 degrees (Manual)
<b>OPTICS:</b>	
PROJECTION LENS	F1.7 - 2.0, f=48.2 - 62.6mm
LENS SHIFT	Up / Down Ratio 1:1 - 10:0 Left / Right 2:3 - 3:2 (Powered)
ZOOM	1.3x Powered
FOCUS	Powered
SCREEN SIZE	31 - 400" (Standard Lens)
PROJECTION DISTANCE	4.6 - 48.2ft (1.4 - 14.7m) /
COVERAGE	100": 11.8 - 15.4ft (3.6 - 4.7m)
THROW RATIO	1.77 - 2.30:1 (Standard Lens)
<b>IMAGE ADJUSTMENTS:</b>	
COLOR MODE	Standard, High Contrast, Cinema, Custom
COLOR ADJUST	RGB Manual
WALL CORRECTION	No
MOUNTING	Ceiling / Rear / Ceiling and Rear / Upward / Downwards
TILT ANGLE	Adjusting feet up to 6.5 degrees
<b>INPUT SIGNALS:</b>	
ANALOG PC INPUT	UXGA/SXGA+/SXGA/WXGA/XGA/SVGA/VGA
SCANNING FREQUENCY	H:15-100 kHz, V:48-100 Hz, Dot clock: 180 MHz
DIGITAL PC INPUT	D-WXGA/D-XGA/D-SVGA/D-VGA
SCANNING FREQUENCY	H:15-100 kHz, V:48-100 Hz, Dot clock: 180 MHz
VIDEO/S-VIDEO INPUT	NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N
COMPONENT INPUT	1080i/1035i/720p/575p/575i/480p/480i
DIGITAL VIDEO INPUT	D-1080i/D-1035i/D-720p/D-575p/D-480p/ D-575i/D480i/D-1080(psf/24)/D-1080(psf/25)/ D-1080(psf/30)
<b>TERMINALS:</b>	
INPUT	
DVI-I 29PIN	Digital PC / Analog PC / Component Input x 1
D-SUB 15PIN	Analog PC / Component Input x 1
RCA X3	Component / Composite Input
MINI DIN 4PIN	S-Video Input
5BNC	Analog PC / Component / Composite Input
OUTPUT	
D-SUB 15PIN	Analog PC Output
<b>CONTROL TERMINAL NETWORK</b>	RS-232C (Dsub9) Yes (Optional Network Adapter)
<b>LAMP:</b>	
TYPE	330W NSHA
LAMP LIFE (QUIET/NORMAL)	3000/2000 Hours
<b>REMOTE CONTROL:</b>	
SENSOR	Wireless Infrared, Front
MOUSE CONTROL	USB
<b>RATINGS:</b>	
FAN NOISE (NORMAL/QUIET)	40/32 dB
POWER CONSUMPTION (NORMAL / QUIET/STAND-BY)	490W / 392W
VOLTAGE	AC 100 to 240V, 50 / 60Hz
<b>TEMPERATURE OPERATING STORAGE</b>	41° to 95° F (5° to 35° C), 20%RH-80%RH -14° to 140° F (-10° to 60° C), 20%RH-80%RH
<b>DIMENSIONS W x D x H</b>	14.6 x 17.3 x 7.4 in. (370 x 440 x 187 mm)
<b>WEIGHT</b>	28.7 lbs (13.0 kg)