

PRODUCT NAME	REALiS SX60
ITEM CODE	1292B002AA
UPC CODE	013803065275



Suggested List Price:
REALiS SX60: \$5,999.00

FEATURES:

- ▲ Improved AISYS Optical Engine: Provides Improved Light Efficiency, Uniformity, and Expanded Color Space
- ▲ Reflective LCD (LCoS) Technology: Larger Aperture for Seamless Images
- ▲ Genuine Canon Optics: 1.7x Powered Zoom Lens with Autofocus
- ▲ Short Throw Distance: Project 100" Screen from only 9.8 feet
- ▲ Home Cinema Mode
- ▲ Quiet Operation: As low as 27dB
- ▲ Auto Setup:
 - Auto Focus, Auto Keystone, Auto Input Signal, Auto Screen Color Correction
- ▲ Direct Power On and Off: Allows You to Turn the Projector On or Off by Simply Plugging or Unplugging the Power Cable
- ▲ Off and Go: An Internal Charging System Automatically Runs the Fan so the Projector can Cool Down without being Plugged In.

CANON CUSTOMER SUPPORT:

- ▲ Canon's Triple P (Projector Protection Program):
 A projector loaner is provided if the original projector is in need of repair
- ▲ 3-Year Parts and Labor Warranty - 120 Day Lamp Life Warranty

CONTENTS OF KIT:

- ▲ REALiS X60 Projector
- ▲ Remote Control (w/ AAA batteries)
- ▲ DVI-VGA Computer Cable
- ▲ Component Video Adapter Cable
- ▲ USB Cable
- ▲ Power Cable
- ▲ Soft Carrying Case
- ▲ 16:9 Mask Adapters
- ▲ Lens Cap
- ▲ Warranty Card

ACCESSORIES:

ITEM CODE NO.	DESCRIPTION	SUGG. LIST PRICE
1312B001AA	RS-LP03 REPLACEMENT LAMP	579.00
0151B001AA	RS-CL02 CEILING PLATE	350.00
0152B001AA	RS-CL03 CEILING PIPE - 14.17 in	150.00
0153B001AA	RS-CL04 CEILING PIPE - 21.65 in	150.00
0154B001AA	RS-CL05 CEILING PIPE - 29.92 in	150.00
1308B001AA	RS-CL06 CEILING MOUNT ADAPTER	849.00
0610B001AA	RS-CA01 RS-232C CABLE	60.00
1310B001AA	RS-NA01 NETWORK ADAPTER	799.00

PACKAGING INFORMATION:

PROJECTOR	W x D x H	WEIGHT
REALiS X60	15.4 x 19.8 x 10.7 in (392 x 502 x 272 mm)	19.2 lbs (8.7kg)

PROJECTOR

SPECIFICATIONS:

BASICS:	
IMAGING DEVICE	0.7" Reflective LCD panels (LCoS) x 3
ASPECT RATIO	4:3
NATIVE RESOLUTION	SXGA+
BRIGHTNESS	2500 ANSI Lumens
UNIFORMITY	88%
CONTRAST	1000:1 / 2000:1 (Home Cinema Mode)
KEystone	
VERTICAL	+/- 20 degrees (Auto/Manual)
HORIZONTAL	+/- 20 degrees (Manual)
OPTICS:	
PROJECTION LENS	F1.85 – 2.5 , f=21.7 – 35.8 mm
LENS SHIFT	9:1, Fixed
ZOOM	1.7x Powered, 12x Digital zoom
FOCUS	Powered (Auto/Manual)
SCREEN SIZE	40" – 300"
PROJECTION DISTANCE	3.9 – 29.5ft (1.2 – 9m) /
COVERAGE	100": 9.8 – 16.1ft (3.0 – 4.9m)
THROW RATIO	1.46 – 2.43:1
IMAGE ADJUSTMENTS:	
COLOR MODE	sRGB, Presentation, Standard, Movie Home Cinema
COLOR ADJUST	Dynamic Gamma, 6-Axis (RGBCMY) Color Adjustment
WALL CORRECTION	Auto
MOUNTING	Ceiling/Rear/Ceiling and Rear
TILT ANGLE	Adjusting feet up to 10 degrees
INPUT SIGNALS:	
ANALOG PC INPUT	UXGA/SXGA+/WXGA/ SXGA/XGA/SVGA/VGA
DIGITAL PC INPUT	SXGA+/SXGA/WXGA/XGA/SVGA/VGA
SCANNING FREQUENCY	H:15~100 kHz, V:50~100 Hz, Dot clock: 170 MHz
VIDEO/S-VIDEO INPUT	NTSC/PAL/SECAM/NTSC4.43/ PAL-M/PAL-N
COMPONENT INPUT	1080i/1035i/720p/575p/480p/575i/480i
DIGITAL VIDEO INPUT	1080i/1035i/720p/575p/480p
TERMINALS:	
INPUT	
DVI-I 29PIN	Digital PC input/Analog PC input/Digital Video input
MINI D-SUB 15PIN	Analog PC input /Component input/ SCART input
RCA X1	Video input
MINI DIN 4PIN	S-Video input
STEREO MINI JACK	Stereo audio input
OUTPUT	
MINI D-SUB 15PIN	Analog PC output
BUILD-IN SPEAKER	1W (Mono)
CONTROL TERMINAL	RS-232C
NETWORK	YES (Optional LAN Adapter)
LAMP:	
TYPE	180W NSH
LAMP LIFE (QUIET/NORMAL)	4000/2500 Hours
REMOTE CONTROL:	
WIRELESS	Wireless Infrared, Front/Back
MOUSE CONTROL	Mouse Control Receiver (USB)
RATINGS:	
FAN NOISE (NORMAL/QUIET)	30/27 dB
POWER	
CONSUMPTION (NORMAL/ QUIET/STAND-BY)	250/225W/7W
VOLTAGE	AC 100 to 240V, 50/60Hz
TEMPERATURE	
OPERATING	41° to 95° F (5° to 35° C)
STORAGE	-22° to 140° F (-30° to 60° C), 5%RH-90%RH
DIMENSIONS W X D X H	8.9 x 13.2 x 4.5 in. (226 x 336 x 114 mm)
WEIGHT	10.1 lbs (4.6 kg)

All prices, specifications, and availabilities subject to change without prior notice.